BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 17 February 2005 (17.02.2005)

PCT

(10) International Publication Number WO 2005/014400 A1

(51) International Patent Classification7: 11/32

B65B 61/24.

(IT). CAVALLARI, Stefano [IT/IT]; Via del Meloncello. 5, I-40135 Bologna (IT).

(21) International Application Number:

PCT/IB2004/002545

(74) Agents: BIANCIARDI, Ezio et al.; Bugnion S.p.A., Via Goito, 18, I-40126 Bologna (IT).

(22) International Filing Date: 5 August 2004 (05.08.2004)

English

(25) Filing Language:

English

(26) Publication Language:

(30) Priority Data: BO2003A000481 6 August 2003 (06.08.2003) IT

(71) Applicant (for all designated States except US): AZIONARIA COSTRUZIONI MACCHINE AU-TOMATICHE [IT/IT]; A.C.M.A. S.p.A., Via Cristoforo Colombo, 1, I-40131 Bologna (IT).


(72) Inventors; and

(75) Inventors/Applicants (for US only): OLEANDRI, Maurizio [IT/IT]; Via Quirino di Marzio, 10, I-40133 Bologna (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ. BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN. CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: A METHOD AND A DEVICE FOR WRAPPING PRODUCTS



(57) Abstract: Products (2) presenting bevelled or rounded corner edges (35) are advanced singly and in succession along a predetermined path (P), each enveloped in a wrapper (11) of parallelepiped box-like shape, and directed ultimately into a station (15) where each product (2) is subjected to a finishing step that consists in deforming at least one part of the wrapper (11) and causing it thus to adhere to the surface of the relative product (2), in particular at the bevelled or rounded corner edges (35); thereafter, the finished products (2) are stacked and wrapped in respective stick packs (36) of which the longitudinal comer edges (38) will hug the corner edges (35) of the stacked products (2), adapting to the contours of the bevelled or rounded profile.